



genesis
XE
PURELEAD

**BATTERY RANGE
SUMMARY**

The Genesis® XE Thin Plate Pure Lead (TPPL) battery excels in demanding environmental and cycling applications such as:

- Short duration UPS, 10 seconds – 5 minutes







Specifications

Battery Design

- 12V pure lead VRLA AGM battery
- UL94 V-0 flame retardant case and cover
- M6 female no-maintenance terminals, 3/8-16 female terminals for XE95
- Can be installed in any orientation except inverted
- Approved for shipping as non-hazardous, nonspillable

Performance Features

- -40°C to 80°C (-40°F to 176°F) with metal jacket
- 300+ full depth of discharge cycles
- High rate charge and discharge
- 2 year shelf life at 25°C (77°F)
- Superior deep discharge recovery
- UL recognized - file No. MH12544



General Specifications

Genesis® XE Battery Type	Nominal Voltage (V)	Nominal Capacity (Ah) 10 hr rate to 1.67Vpc @ 25°C/77°F	Nominal Dimensions						Overall Weight		Torque		Internal Resistance (mΩ)	Typical Short Circuit Current (A)
			Length		Width		Height		kg	lbs	in-lbs	Nm		
XE13	12	13	175.0	6.89	83.1	3.27	129.0	5.08	5.4	11.9	50	5.6	9.0	1400
XE16	12	16	180.8	7.12	75.9	2.99	166.9	6.57	6.4	14.1	50	5.6	7.5	1600
XE30	12	28	165.9	6.53	175.0	6.89	125.0	4.92	10.2	23.3	60	6.8	5.0	2400
XE40	12	42	196.6	7.74	165.1	6.50	169.9	6.69	16.1	35.4	60	6.8	4.5	2600
XE60	12	62	275.6	10.85	171.7	6.76	180.8	7.12	22.4	49.4	60	6.8	2.5	3100
XE70	12	68	328.7	12.94	166.1	6.54	174.0	6.85	25.7	56.6	60	6.8	3.5	3500
XE95	12	95	329.9	12.99	172.5	6.79	218.9	8.62	35.1	77.4	60	6.8	2.2	5000

Constant Power Discharge Performance

Constant power discharge rate – KW/Cell to 1.67VPC at 25°C (77°F)

Genesis® XE Battery Type	Seconds					Minutes						
	10	15	20	30	45	1	1.5	2	3	4	5	
XE13	0.287	0.279	0.269	0.253	0.234	0.218	0.193	0.172	0.141	0.120	0.105	
XE16	0.351	0.341	0.332	0.315	0.295	0.278	0.249	0.225	0.187	0.161	0.140	
XE30	0.546	0.533	0.520	0.496	0.468	0.444	0.398	0.361	0.303	0.260	0.227	
XE40	0.836	0.827	0.811	0.781	0.739	0.700	0.633	0.578	0.493	0.429	0.379	
XE60	1.202	1.185	1.165	1.123	1.069	1.019	0.928	0.852	0.728	0.630	0.553	
XE70	1.188	1.167	1.147	1.110	1.060	1.014	0.935	0.866	0.753	0.664	0.591	
XE95	1.484	1.472	1.451	1.412	1.360	1.312	1.226	1.147	1.014	0.908	0.819	

Constant Power Discharge Performance

Constant power discharge rate – 480V Nominal System KWB to 400V at 25°C (77°F)

Genesis® XE Battery Type	Seconds					Minutes						
	10	15	20	30	45	1	1.5	2	3	4	5	
XE13	69	67	65	61	56	52	46	41	34	29	25	
XE16	84	82	80	76	71	67	60	54	45	39	34	
XE30	131	128	125	119	112	107	95	87	73	62	54	
XE40	201	198	195	187	177	168	152	139	118	103	91	
XE60	288	284	280	270	257	245	223	204	175	151	133	
XE70	285	280	275	266	254	243	224	208	181	159	142	
XE95	356	353	348	339	326	315	294	275	243	218	197	

Charge Voltage

Cyclic use: 14.7V to 15.0V at 25°C (77°F) No current limit

Float use: 13.5V to 13.8V at 25°C (77°F) No current limit



www.enersys.com

EnerSys
2366 Bernville Road
Reading, PA 19605
USA
Tel: +1-610-208-1991
+1-800-538-3627
Fax: +1-610-372-8613

EnerSys EMEA
Löwenstrasse 32
8001 Zürich - Switzerland
Tel: +41 44 215 74 10

EnerSys Asia
152 Beach Road
Gateway East Building #11-03
Singapore 189721
Tel: +65 6508 1780

Distributed by:

Printed in USA
© 2012 EnerSys. All rights reserved.
Trademarks and logos are the property of
EnerSys and its affiliates except ISO™
which is not the property of EnerSys.